



Project	
Notes	
Type	Date
Cat. No.	

PDD™ Series

Decorative Pendant Light

DESCRIPTION

The PDD series is a ceiling pendant series which can be used in a broad range of residential and commercial applications. This series provides customers with a high quality luminaire utilizing the latest LED, solid state lighting and electronic driver technology for optimal performance and maximized energy efficiency.

Specification Features

Construction

Contemporary decorative pendant fixture with brushed nickel finished steel pans and opal glass diffusers. Lens design and materials provide uniform appearance without pixelation.

Qualifications

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard.

Electrical

Equipped standard with 120V 10-100% dimming driver.

Installation

Designed for wall or ceiling mounting on 4" electrical J-Box.

Warranty

3-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).



PDD Series

(528 Lumens)

Rated Life 50,000 hours
 Limited Warranty 3 years
 Efficacy Up to 70 LPW
 Dimming Continuous



Quick Ship

PDD-MB-120-BN

Ordering Information

Example: PDD-MB-120-BN

PDD		120D		BN
Series PDD Decorative Pendant Fixture	Rated Wattage BLANK- Medium Base Bulb 8- 8W LED Module	Driver Type 120D- 120V, Triac Dimming	Color Temp BLANK- Medium Base 930- 90+ CRI, 3000K	Finish BN- Brushed Nickel

Specifications and Dimensions subject to change without notice.

Performance Summary

Input Voltage	120V
Input Frequency	50/60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table >
Efficacy	70 LPW (typ.)
CRI	90+, R9 > 0
Available CCT ¹	2700/3000/3500/4000/5000K
Color Consistency ²	5-step MacAdam Ellipse
Rated Life	50,000 hours
L70 ³	> 72,000 hours or > 45,000
Power Factor	>0.71
THD	< 20%
Dimming	120V Dimming (10-100%)
Operating Temp.	-18°C to 40°C

Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)	Delivered Lumens	Efficacy (lm/W)
Opal	13"	PDD-8-120D-930-BN	8	528	66

NOTES:

- ¹ Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- ² Energy star listed
- ³ Quick ship: Made To order Only
- ⁴ Typical color consistency. May vary or be changed.
- ⁵ L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information
- ⁶ NOTE: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.



Specifications and Dimensions subject to change without notice.

Product Dimensions

PDD

Coming Soon

