


PROJECT	NOTES	TYPE	DATE	CAT. No.
---------	-------	------	------	----------



# LSV

## LED Square Vanity

The LSV Series tiered contemporary framed wall mounted vanity fixture and is available in brushed nickel and black. Updated with the latest in LED technology. The long LED life coupled with exceptional color rendering make this fixture attractive for new or retrofit projects. The LSV is an elegant lighting solution that can be used in various applications including corridors and restrooms. Fixture mounts to standard junction box (not included).




INPUT VOLTAGE	120V
INPUT FREQUENCY	50/60 Hz
RATED WATTAGE	See Performance Data
DELIVERED LUMENS	See Performance Data
EFFICACY	96 LPW (typ.)
CRI	90
AVAILABLE CCT	2700K, 3000K, 3500K, 4000K, 5000K
LENS TYPE	Plastic

RATED LIFE	30,000hrs (Based on 3hrs a Day)
L70	>50,000hrs
POWER FACTOR	>0.9
THD	<20%
DIMMING	N/A
OPERATING TEMP.	-4°F - 113°F / -20°C to 45°C
BEAM ANGLE	N/A

### ORDER INFO / EXAMPLE: LSV-24-20-120-MCT-BN

SERIES	FORM FACTOR	RATED WATTAGE	DRIVER TYPE	COLOR TEMP	FINISH
LSV	24	20	120	MCT	BN
LSV LED Square Vanity	24-24" Length 36-36" Length	24" Housing 20- 18W, 1800 Lumens 36" Housing 26- 26W, 2600 Lumens	120- 120V	MCT- 2700K, 3000K, 3500K, 4000K, 5000K CCT Selectable 90CRI	BN- Brushed Nickel BL- Black



	A	B	C	Case QTY
RVL-24	25.5" L	4.5" D	4.2" H	6
RVL-36	37.5" L	4.5" D	4.2" H	6

## PERFORMANCE DATA

FORM FACTOR	KELVIN	RATED WATTAGE	DELIVERED LUMENS	EFFICACY (L/M/W)
24"	27K-5K	18W	1800	100
36"	27K-5K	26W	2600	100

## QUICK SHIP

LSV-24-20-120-MCT-BN	LSV-24-20-120-MCT-BL
LSV-36-26-120-MCT-BN	LSV-36-26-120-MCT-BL

## ADDITIONAL IMAGES



Made to order items. Minimum 90 day lead time.  
 Minimum order quantity may vary please contact sales.  
<sup>1</sup> DLC Listed / <sup>2</sup> DLC Premium Listed / <sup>3</sup> Title 24 / <sup>4</sup> JA8 & Title 24  
 Typical color consistency. May vary or be changed. L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact GlobaLux for detailed information.  
 Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.

### CONSTRUCTION

Single ring surround a milk white acrylic diffuser with decorative end caps provides widespread and even illumination. Lens design and materials provide uniform illumination without pixelation.

### ELECTRICAL

Equipped standard with 120V fixed output driver operating at 60Hz.

### QUALIFICATIONS

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Suitable for closets according to NEC Section 410.8 & 410.16. Adheres to LM70, LM80 and TM21 industry standards. ENERGY STAR® certified product (for 3000K and 4000K only) and Title 24 qualified. Dedicated 120V Models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications. California Title 24 Compliant, JA8 compliant. CEC Listed.

### INSTALLATION

Designed for wall mounting on 4" electrical J-Box.

### WARRANTY

5-year Limited Warranty. See warranty documentation for more info.

## COMPATIBLE JUNCTION BOXES



4" PVC



4" Octagon



4" PVC Ceiling Box



3-1/2" Octagon



4" Round Pancake



4" Octagon / V Bracket

## PHOTOMETRIC DATA

LSV-24-20-120-MCT

Made to order items. Minimum 90 day lead time. Minimum order quantity may vary please contact sales.

<sup>1</sup> DLC Listed / <sup>2</sup> DLC Premium Listed / <sup>3</sup> Title 24 / <sup>4</sup> JA8 & Title 24 / Typical color consistency. May vary or be changed.

L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact Globalux for detailed information. / Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.