LXS

BI-COLOR LED EXIT SIGN


COMMERCIAL · LOW ENERGY · QUICK INSTALLATION · UNIVERSAL MOUNTING

PROJECT | TYPE | NOTES | DATE | CAT. NO.









	A	B	C	Case QTY
LCXS	11-5/8" W	7-1/8" H	1-5/8" D	6

LISTINGS & COMPLIANCE

- **UL 924** EMERGENCY
- **NFPA 101** LIFE SAFETY
- **DAMP** LOCATION
- **5 YEAR** WARRANTY
- **TITLE 20** CERTIFIED

HOUSING COLOR

W — White

B — Black
No photo on file

Bi-color. Green / red lettering selectable; EZ snap-out chevron directional indicators.

The LXS series is a compact, low-profile exit sign that combines an attractive, easy-to-install contemporary design with proven, ultra-reliable electronics for energy-efficient emergency lighting. LXS units are completely self-contained and feature universal mounting with canopy included. Ideal for applications requiring an attractive, quick-installation exit sign with low energy consumption.

1W	Green / Red	2	90 min
RATED WATTAGE	SELECTABLE LETTERING	FACES	BATTERY BACKUP

SPECIFICATIONS LXS

CONSTRUCTION

Housing	Injection-molded 5VA flame-retardant, high-impact thermoplastic
Panel / Faces	2 faces; curved face, rounded corners
Directional	EZ snap-out chevron indicators

ELECTRICAL

Input Voltage	120–277V (dual 120/277)
Input Frequency	50/60 Hz
Rated Wattage	1W
Power Factor	> 0.45
THD	N/A

EMERGENCY

Battery	1.2V long-life NiCad, maintenance-free
Runtime	90 min minimum (select models) · AC only option
Charger	Two-rate solid-state; recharges in 24 hrs
Testing	Push-to-test switch · charge/power-on LED

OPTICAL

Lettering	Green / Red selectable
CRI	> 70
Beam Angle	120°

INSTALLATION

Mounting	Universal knockout back plate (J-box) · EZ-snap canopy, top or end
Operating Temp.	32°F – 104°F / 0°C – 40°C

LISTINGS & COMPLIANCE

Emergency	UL 924
Codes	NFPA 101 Life Safety Code · NEC · OSHA
Energy	California Title 20 certified
Location	Damp location (0°C – 40°C)
Rated Life / L70	30,000 hrs (3 hrs/day) · L70 N/A
Warranty	5-Year electronics & housing · battery pro-rated

DIMENSIONS

CATALOG	WATTS	A — WIDTH	B — HEIGHT	C — DEPTH	CASE
LXS	1W	11-5/8"	7-1/8"	1-5/8"	6

COMMERCIAL · LOW ENERGY · QUICK INSTALLATION · UNIVERSAL MOUNTING

MODEL NUMBERS QUICK SHIP

CATALOG NUMBER	DESCRIPTION	FACES	HOUSING	LETTERING	CASE QTY	AVAILABILITY
LXS-2-W-GR	Bi-color LED exit sign, 90-min battery	2	White	Green / Red selectable	6	STOCK

ORDERING EXAMPLE: LXS-2-W-GR

POSITION	CODE	DESCRIPTION
Series	LXS	LED Exit Sign
Faces	2	2 faces
Housing Color	W / B	White / Black
Lettering	GR	Green / Red, selectable
Options	blank / AC	90-minute battery backup / AC only

Made to order items. Minimum 90-day lead time. Minimum order quantity may vary — contact sales.

QUALIFICATIONS

Meets UL 924, NFPA 101 Life Safety Code, NEC, OSHA, local and state codes. UL listed for damp locations (0°C – 40°C). California Title 20 certified.

WARRANTY

COMPONENT	TERM
Electronics & housing	5-Year Limited
Battery	Pro-rated 5 years

See warranty documentation for more info.

DOWNLOADS & PHOTOMETRICS

SCAN FOR LXS ASSETS

Full LM-79 reports and IES photometric files are published per catalog number at the link above.

Spec Sheet (this document)	PDF
Photometric Files	IES / LDT
Installation Instructions	PDF
Product Photography	JPG / PNG
Warranty Statement	PDF
Revit / BIM Family	TBD

INTERNAL PROOF NOTE — NOT FOR PUBLICATION. Exit sign — no photometrics in source; set to not applicable. Source dimension table row is labeled 'LCXS' (copy error) — values used for LXS; confirm. Source cites 'NFPA 11' — corrected to NFPA 101. Emergency illumination stated 'on select models'. Black housing has no photo. Open items: Finish photos (no Black (B) photo).