WXS

WET LOCATION EXIT & EXIT/EMERGENCY

WET LOCATIONS · AC ONLY OR BATTERY BACKUP · WALL MOUNT


WXS · REV 2026 1110

PROJECT | TYPE | NOTES | DATE | CAT. NO.









The WXS (Wet Location Exit Sign) series is engineered to perform in the most extreme environments. A fully gasketed polycarbonate lens and ABS housing allow the WXS to be installed in locations that require wet location rated protection. Ideal for wet location areas requiring AC-only or battery-backup exit signs that are subject to saturation with non-mechanically delivered water.

3.5W	Red / Green	WET	90 min
RATED WATTAGE	LETTERING	LOCATION RATED	BATTERY BACKUP

LISTINGS & COMPLIANCE

- **UL 924** EMERGENCY
- **NFPA 101** LIFE SAFETY
- **WET** LOCATION
- **5 YEAR** WARRANTY
- **TITLE 20** CERTIFIED

HOUSING & LETTERING

— — Grey housing
UV-stabilized polycarbonate



R — Red lettering

G — Green lettering
No photo on file

Fully gasketed. Polycarbonate lens and housing rated for wet locations; knockouts for conduit feed.

SPECIFICATIONS WXS

CONSTRUCTION

Housing	5VA flame-retardant, UV-stabilized polycarbonate, grey
Panel / Faces	High-impact UV-stabilized clear PC lens, gasketed
Directional	EZ snap-out chevron indicators
Conduit	Knockouts for conduit feed

ELECTRICAL

Input Voltage	120–277V (dual 120/277)
Input Frequency	50/60 Hz
Rated Wattage	3.5W
Power Factor	> 0.45
THD	N/A

EMERGENCY

Battery	3.6V long-life NiCad, maintenance-free
Runtime	90 min minimum (blank) · AC only option
Charger	Two-rate solid-state; recharges in 24 hrs
Testing	Push-to-test switch · charge/power-on LED

OPTICAL

Lettering	Red / Green
CRI	> 70
Beam Angle	120°

INSTALLATION

Mounting	Back surface wall mount, hardware provided
Operating Temp.	32°F – 104°F / 0°C – 40°C

LISTINGS & COMPLIANCE

Emergency	UL 924
Codes	NFPA 101 Life Safety Code · NEC · OSHA
Energy	California Title 20 certified
Location	Wet location (9°C – 40°C as stated)
Rated Life / L70	30,000 hrs (3 hrs/day) · L70 N/A
Warranty	5-Year Limited

DIMENSIONS

CATALOG	WATTS	A — HEIGHT	B — WIDTH	C — DEPTH	CASE
WXS	3.5W	8.70"	12.60"	2.6"	6

WET LOCATIONS · AC ONLY OR BATTERY BACKUP · WALL MOUNT

MODEL NUMBERS QUICK SHIP

CATALOG NUMBER	DESCRIPTION	LETTERING	BATTERY	CASE QTY	AVAILABILITY
WXS-R	Wet location LED exit sign	Red	90-min battery	6	STOCK

ORDERING EXAMPLE: WXS-R

POSITION	CODE	DESCRIPTION
Series	WXS	Wet Location Exit
Lettering	R / G	Red / Green
Battery	blank / AC	90-minute battery / AC only

COMPATIBLE JUNCTION BOXES



4" PVC



4" Octagon



4" PVC Ceiling Box



3-1/2" Octagon



4" Round Pancake



4" Octagon / V Bracket

Reference list only. Confirm the fixture works safely with the box used.

Made to order items. Minimum 90-day lead time. Minimum order quantity may vary — contact sales.

QUALIFICATIONS

Meets UL 924, NFPA 101 Life Safety Code, NEC, OSHA, local and state codes. UL listed for wet locations (9°C – 40°C, as stated). California Title 20 certified.

WARRANTY

COMPONENT	TERM
Unit	5-Year Limited

See warranty documentation for more info.

DOWNLOADS & PHOTOMETRICS

SCAN FOR WXS ASSETS

Full LM-79 reports and IES photometric files are published per catalog number at the link above.

Spec Sheet (this document)	PDF
Photometric Files	IES / LDT
Installation Instructions	PDF
Product Photography	JPG / PNG
Warranty Statement	PDF
Revit / BIM Family	TBD

INTERNAL PROOF NOTE — NOT FOR PUBLICATION. Exit sign — no photometrics; set to not applicable. Wet-location range in source reads 9°C – 40°C (possible typo for 0°C) vs operating temp 0°C – 40°C — confirm. Housing colour 'grey' per text, swatch approximate. Title says 'Exit & Exit/Emergency' but no separate combo model is listed. Source cites 'NFPA 11' — corrected to NFPA 101. Open items: Finish photos (no grey housing swatch photo; no green lettering photo).