EXS

EDGE LIT LED EXIT SIGN


RETAIL · OFFICES · MEDICAL FACILITIES · COMMERCIAL SPACES

PROJECT | TYPE | NOTES | DATE | CAT. NO.









The EXS series is a surface-mount, edge-lit LED exit sign with an architectural, slim design that fits any environment, offering specification-grade aesthetics with in-field installation flexibility. Completely self-contained, it uses reliable, energy-efficient LED illumination. Typical installations include retail, offices and medical facilities, or any space where an upgraded appearance is desired.

1 or 2	Red / Green	90 min	120–277V
FACES	LETTERING	BATTERY BACKUP	INPUT VOLTAGE

LISTINGS & COMPLIANCE

- **cULus** LISTED
- **UL 924** EMERGENCY
- **DAMP** LOCATION
- **5 YEAR** WARRANTY
- **TITLE 20** CERTIFIED

HOUSING COLOR



A — Aluminum

W — White
No photo on file

B — Black
No photo on file

FACES

1 — single face, transparent panel · 2 — double face, mirror panel. Self-adhesive chevron appliqués and guide template provided.

SPECIFICATIONS EXS

CONSTRUCTION

Housing	Premium extruded aluminum (black / white powder coat optional)
Panel / Faces	Edge-lit; 1 face transparent · 2 face mirror
Directional	Self-adhesive chevron appliqués + template

ELECTRICAL

Input Voltage	120–277V (dual 120/277)
Input Frequency	50/60 Hz
Rated Wattage	3W (3.5W in performance data)
Power Factor	> 0.45
THD	N/A

EMERGENCY

Battery	4.8V long-life NiCad, maintenance-free
Runtime	90 min minimum (blank) · AC only option
Charger	Two-rate solid-state; recharges in 24 hrs
Testing	Push-to-test switch · charge/power-on LED

OPTICAL

Lettering	Red / Green
CRI	> 70
Beam Angle	120°

INSTALLATION

Mounting	Aluminum canopy included — top, end or back mount
Operating Temp.	32°F – 104°F / 0°C – 40°C

LISTINGS & COMPLIANCE

Emergency	UL 924
Codes	NFPA 101 Life Safety Code · NEC · OSHA
Energy	California Title 20 certified
Location	Damp location (0°C – 50°C)
Rated Life / L70	30,000 hrs (3 hrs/day) · L70 N/A
Warranty	5-Year electronics & housing · battery pro-rated

DIMENSIONS

CATALOG	WATTS	A — WIDTH	B — HEIGHT	C — DEPTH	CASE
EXS	3.5W	12.7"	10.74"	1.64"	6

RETAIL · OFFICES · MEDICAL FACILITIES · COMMERCIAL SPACES

MODEL NUMBERS QUICK SHIP

CATALOG NUMBER	DESCRIPTION	FACES	HOUSING	LETTERING	CASE QTY	AVAILABILITY
EXS-1-A-G	Edge-lit LED exit sign, 90-min battery	1	Aluminum	Green	6	STOCK
EXS-1-A-R	Edge-lit LED exit sign, 90-min battery	1	Aluminum	Red	6	STOCK
EXS-2-A-G	Edge-lit LED exit sign, 90-min battery	2	Aluminum	Green	6	STOCK
EXS-2-A-R	Edge-lit LED exit sign, 90-min battery	2	Aluminum	Red	6	STOCK

No battery suffix = 90-minute battery backup per order grid.

ORDERING EXAMPLE: EXS-1-A-R-AC

POSITION	CODE	DESCRIPTION
Series	EXS	Edge Lit LED Exit Sign
Faces	1 / 2	1 face (transparent panel) / 2 faces (mirror panel)
Housing Color	A / W / B	Aluminum / White / Black
Lettering	R / G	Red / Green
Battery	blank / AC	90-minute battery backup / AC only

COMPATIBLE JUNCTION BOXES


4" PVC


4" Octagon


4" PVC Ceiling Box


3-1/2" Octagon


4" Round Pancake


4" Octagon / V Bracket

Reference list only. Confirm the fixture works safely with the box used.

Made to order items. Minimum 90-day lead time. Minimum order quantity may vary — contact sales.

QUALIFICATIONS

Meets UL 924, NFPA 101 Life Safety Code, NEC, OSHA, local and state codes. UL listed for damp locations (0°C – 50°C). California Title 20 certified.

WARRANTY

COMPONENT	TERM
Electronics & housing	5-Year Limited
Battery	Pro-rated 5 years

See warranty documentation for more info.

DOWNLOADS & PHOTOMETRICS

SCAN FOR EXS ASSETS

Full LM-79 reports and IES photometric files are published per catalog number at the link above.

Spec Sheet (this document)	PDF
Photometric Files	IES / LDT
Installation Instructions	PDF
Product Photography	JPG / PNG
Warranty Statement	PDF
Revit / BIM Family	TBD

INTERNAL PROOF NOTE — NOT FOR PUBLICATION. Exit sign — no photometrics in source; set to not applicable. Rated wattage 3W (spec table) vs 3.5W (performance data) — confirm. Operating temp 0–40°C vs damp listing 0–50°C as in source. Source cites 'NFPA 11' — corrected to NFPA 101. White/Black housings have no photos. Open items: Finish photos (no W / B housing photos).