



Project	
Notes	
Type	Date
Cat. No.	

CVL™ Series **Curved Glass Vanity Light**

DESCRIPTION

The CVL Bathroom Vanity Light brings a graceful, contemporary touch to a range of interior styles. Its curved soft white glass shades are complemented by sleek metal components. This fixture is available in a variety of finishes and sizes and can be installed facing up.



Specification Features

Construction

White Glass shades surround an elongated aluminum bar and mounting plate. Lens design and materials provide uniform appearance without pixelation.

Qualifications

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. Dedicated 120V Models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications. LED Models are Energy Star Qualified.

Warranty

3-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

Electrical

Equipped standard with 120V fixed output driver operating at 60 Hz.

Installation

Designed for wall mounting on 4" electrical J-Box.

Rated Life 60,000 hours
Limited Warranty 3 years

Quick Ship

Ordering Information

Example: CVL-3-24-120-830-BN

CVL	2	8	120D	30	BN
Series CVL Curved Glass Vanity Light	Form Factor 1- 1 Light 2- 2 Light 3- 3 Light 4- 4 Light	Lamp Configuration MB-E26 Medium Socket 8- 1x8W LED 16- 2x8W LED 24- 3x8W LED 32- 4x8W LED	Driver Type 120D- 120V Triac Dimming ¹	Color Temp Blank- Blank for MB Configurations 830- 80 CRI, 3000K (For LED Configurations Only)	Finish BN-Brushed Nickel

Specifications and Dimensions subject to change without notice

Performance Summary

Input Voltage	120V
Input Frequency	50/60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table
Efficacy	70 LPW
CRI	80+, (LED Models)
Available CCT1	3000K, 4000K
Color Consistency ²	5-step MacAdam Ellipse
Rated Life	50,000
L70 ³	> 72,000 hours or > 45,000 >
Power Factor	0.9
THD	< 20%
Dimming	120V Dimming(15-100%)
Operating Temp.	-18°C to 40°C

NOTES:

- ¹ Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- ² Energy star listed
- ³ Quick ship: 3000K. Other CCTs may require a lead time or be special order
- ⁴ Typical color consistency. May vary or be changed.
- ⁵ L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information



Specifications and Dimensions subject to change without notice

Product Dimensions

Form Factor	1 Light Configuration	2 Light Configuration	3 Light Configuration	4 Light Configuration
Mounting Orientation	Up	Up	Up	Up
Dimensions	Length: 8-1/4"	Length: 19"	Length: 28-3/4"	Length: 39"
	Height: 6"	Height: 6"	Height: 6"	Height: 6"
	Depth: 5"	Depth: 5"	Depth: 5"	Depth: 5"