



Project	
Notes	
Type	Date
Cat. No.	

OWS™ Series

Outdoor Wall Sconce



OWS Series

9W(800 Lumens)

DESCRIPTION

The OWS Series is a contemporary wall sconce fixture updated with the latest in LED technology. The OWS provides accent illumination that visually expands the space and creates a relaxing atmosphere. The long LED life coupled with exceptional color rendering make this fixture attractive for new or retrofit projects. Ideal for use in hallways, stairways, dining areas, foyers and meeting rooms for residential and commercial applications.



Specification Features

Construction

Contemporary styled fixture. Two twin steel rings surrounded a high-transmission frosted plastic diffuser designed to eliminate glare and optimize lumen output.

Qualifications

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. ENERGY STAR® certified product (for 3000K and 4000K only) and Title 24 qualified. Dedicated 120V Models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications. California Title 24 Compliant, JA8 compliant, CEC Listed.

Warranty

3-year Limited Warranty. See warranty documentation for more information.

Electrical

Equipped standard with 120V driver on board.

Installation

Designed for wall mounting on 4" electrical J-Box.

Rated Life 50,000 hours
 Limited Warranty 3 years
 Efficacy Up to 88 LPW

Quick Ship

OWS-9-120-830/40/50-BR

While Supplies Last

Ordering Information

Example: OWS-9-120-830/40/50-BR

OWS	9	120	830 /40/50	GY
Series OWS Outdoor Wall Sconce	Rated Wattage 9- 9W,(795 Lumens)	Driver Type 120- 120V ²	Color Temp MCT- 80+ CRI, 3000K, 4000K, 5000K Color Selectable ²	Finish BR- Bronze

Specifications and Dimensions subject to change without notice.

Performance Summary

Input Voltage	120V
Input Frequency	50/60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table
Efficacy	88 LPW (typ.)
CRI	80+, R8 > 0
Available CCT	3000K, 4000K, 5000K
Color Consistency	5-step MacAdam Ellipse
Rated Life	50,000 hours
L70	> 72,000 hours or > 45,000
Power Factor	> 0.9
THD	< 20%
Dimming	N/A
Operating Temp.	-18°C to 40°C

Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)	Delivered Lumens	Efficacy (lm/W)
Frosted Glass		OWS-17-120-830/40/50	9	795	88.33

NOTES:

- ¹ Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- ² Energy star listed
- ³ Quick ship
- ⁴ Typical color consistency may vary or changed.
- ⁵ L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information
- ⁶ Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.



Specifications and Dimensions subject to change without notice.

Product Dimensions

OWS-9

