

SAFETY INSTRUCTIONS

PLEASE READ THESE INSTRUCTIONS CAREFULLY AND SAVE THEM, AS YOU MAY NEED THEM AT A LATER DATE.

1. WARNING:

Failure to install and wire fixture in accordance with the National Electrical Codes (NEC), all applicable Federal, State and Local electrical codes, as well as Specific U.L. safety standards for the intended working environment (location/application) may cause serious personal injury, death and/or property damage. This product must be installed by a person familiar with the construction and operation of the product and the hazards involved. This product is for use on 120V 60Hz circuits only. Risk of fire and electrical shock. Most dwellings built before 1985 have supply wires rated 60 degrees c. Consult a qualified electrician before installing. If supply wires are located within 3 inches to the ballast use wires rated at least 90 degrees C.

2. CAUTION:

TURN OFF POWER FROM THE MAIN CIRCUIT BEFORE INSTALLING FIXTURE.

Make sure fixture is grounded per National Electrical Codes (NEC).

3. CAUTION:

These fixtures are intended to be mounted to a metal outlet box. The box must be directly supported by the building structure. This fixture is suitable for damp and dry location. This is not a wet location fixture

4. IMPORTANT NOTE:

The safeguards and instructions appearing in this page, are not meant to cover all possible conditions and situations that may occur. It may be understood that common sense, cautions and care are factors, which cannot be built into any product. The person(s) installing, operation and responsible for the light fixture, must execute these factors.

NEEDED TOOLS

- Safety Glasses
- Ruler/Tape Measure
- Flat Blade Screwdriver
- Phillips Screwdriver
- Adjustable Wrench
- Drill
- 3/16" Drill Bit
- 3/32" Drill Bit
- Pliers



Wire Connector
2pcs

TURN OFF POWER FROM THE MAIN CIRCUIT BEFORE INSTALLING FIXTURE.

1. To help prevent the possibility of electrical shock it is recommended to use rubber sole shoes.
2. Exercise care when handling the fixture to avoid cuts or abrasions.
3. Electrical connections, attach the green or bare copper wire to the ground screw on the cross bar. (Ground must be securely attached or unit may not work properly) Connect white supply wire to white fixture wire, cover the wires with wire nut/or twist wires together and cover really well with Electrical tape. Connect black supply wire to black fixture wire, cover the wires with wire nut/or twist wires together and cover really well with Electrical tape. Make sure on both connections no wires are exposed at all. Push connected wires back into electrical box.
4. Turn the mounting screws through the oval holes to the outlet box. Tighten the screws.
5. Carefully slide the Glass Lens in from the top of fixture.
6. Turn power on.

