



Project	
Notes	
Type	Date
Cat. No.	

TDL™ Series

4" Temporary Disk Light

DESCRIPTION

The TDL series is a solution to an ongoing hassle. Install over the J-box and it doesn't have to be removed until you are ready to install a permanent light fixture. Two screws and quick connects make installation easy. Unlike permanent lighting, temporary lighting is installed on a job site while working to ensure maximum illumination while working. The ability to keep the temporary fixture installed until after sheet rock is installed ensures maximum utility.



TDL Series

4" Housing
10W (700 Lumens)

Specification Features



Construction

Steel housing with diffusion lens for Optimal visual comfort while providing uniform light output. Lens design and materials provide uniform appearance without pixelation.

Qualifications

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling is standard. Dedicated 120V Models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications.

Warranty


3-year Limited Warranty. See warranty documentation for more information.

Electrical

Equipped standard with 120V on-board module.

Installation

4" models are designed for mounting on standard octagonal junction box.



Rated Life 27,000 hours
Limited Warranty 3 years
Efficacy Up to 70 LPW

Quick Ship
TDL-4-10-120-840-WH

Ordering Information

Example: TDL-4-10-120-840-WH

TDL	4	10	120	8	40	WH
Series	Size	Rated Wattage	Driver Type	CRI	Color Temp	Finish
TDL Temp Disk Light	4-4"	4" Housing 10- 10W (700 Lumens)	120-120V	8 80+ CRI ^{1, 2}	40-4000K	WH- White
Options						

Specifications and Dimensions subject to change without notice.

Performance Summary

Input Voltage	120V
Input Frequency	50/60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table
Efficacy	70 LPW
CRI	80+ CRI
Available CCT ¹	4000K
Color Consistency ²	5-step MacAdam Ellipse
Rated Life	27,000 hours
L70 ³	> 72,000 hours or > 45,000
Power Factor	>0.99
THD	< 20%
Dimming	N/A
Operating Temp.	-20°C to 40°C

Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)	Delivered Lumens	Efficacy (lm/W)
Acrylic	4"	TDL-4-10-120-840-WH	10W	700	70

NOTES:

- ¹ Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- ² Energy star listed
- ³ Quick ship: 4000K. Other CCTs may require a lead or special order
- ⁴ Typical color consistency. May vary or be changed.
- ⁵ L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information
- ⁶ Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.



Specifications and Dimensions subject to change without notice.

Product Dimensions

TDL-4



GlobaLux
LIGHTING

© 2019 GlobaLux Lighting, LLC. All rights reserved. For informational purposes only. Reproduction in whole or part is prohibited without prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequences of its use. GlobaLux Lighting reserves the rights make changes in specification at any time without notice.

GlobaLux Lighting LLC
www.globaluxlighting.com
773 S. Benson Ave
Ontario, CA 91761
Ph: 909-591-7506