



Project	
Notes	
Type	Date
Cat. No.	

WSR™ Series

Wall Sconce Round

DESCRIPTION

The WSR Series tiered contemporary framed wall mounted sconce fixture is available in brushed nickel to pair with popular bath hardware. Updated with the latest in LED technology. The long LED life coupled with exceptional color rendering make this fixture attractive for new or retrofit projects. The WSR is an elegant lighting solution that can be used in various applications including corridors and restrooms. Fixture junction box not included.



WSR Series
14" Length
 13W, 910 Lumens

Specification Features



Construction

Aluminum housing with translucent acrylic diffuser. Lens design and materials provide uniform illumination without pixelation.

Electrical

Equipped standard with 120V fixed output driver operating at 60 Hz.

Qualifications

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling. Adheres to LM70, LM80, and TM21 industry standards. ENERGY STAR® certified product (for 3000K and 4000K only) and Title 24 qualified. Dedicated 120V Models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications. California Title 24 Compliant, JAS compliant, CEC Listed.

Installation

Designed for wall mounting on 4" electrical J-Box.

Rated Life 50,000 hours
 Limited Warranty 3 years
 Efficacy up to 70 LPW

Warranty

3-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

Quick Ship

Ordering Information

Example: WSR-14-13-120-930-NS

WSR	14	13	120	9	30	NS
Series	Form Factor	Rated Wattage	Driver Type	CRI	Color Temp	Finish
WSR Wall Sconce Round	14- 14" Length	14" Housing 13- 13W, (910 Lumens)	120- 120V ¹	9- 90+ CRI	30- 3000K	BN- Brushed Nickel

Specifications and Dimensions subject to change without notice

Performance Summary

Input Voltage	120V
Input Frequency	50/60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table
Efficacy	70 LPW
CRI	90+, R9 > 0
Available CCT ¹	3000K
Color Consistency ²	5-step MacAdam Ellipse
Rated Life	50,000
L70 ³	> 72,000 hours or > 45,000 >
Power Factor	0.9
THD	< 20%
Dimming	N/A
Operating Temp.	-18°C to 40°C

Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)	Delivered Lumens	Efficacy (lm/W)
Frosted Acrylic	14"	WSR-14-13-120-MCT-BN	13W	910	70

NOTES:

- ¹ Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- ² Energy star listed
- ³ Quick ship: 3000K. Other CCTs may require a lead time or be special order
- ⁴ Typical color consistency. May vary or be changed.
- ⁵ L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information



Specifications and Dimensions subject to change without notice

WSR-14

