



Project	
Notes	
Type	Date
Cat. No.	

WSS™ Series

Wall Sconce Square

DESCRIPTION

The WSS Series tiered contemporary framed wall mounted sconce fixture is available in brushed nickel to pair with popular bath hardware. Updated with the latest in LED technology. The long LED life coupled with exceptional color rendering make this fixture attractive for new or retrofit projects. The WSS is an elegant lighting solution that can be used in various applications including corridors and restrooms. Fixture junction box not included.



WSS Series

14" Length
13W, 910 Lumens

Rated Life 50,000 hours
Limited Warranty 3 years
Efficacy up to 70 LPW

Quick Ship



Specification Features

Construction

Aluminum housing with translucent acrylic diffuser. Lens design and materials provide uniform illumination without pixelation.

Qualifications

All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Damp location labeling. Adheres to LM70, LM80, and TM21 industry standards. ENERGY STAR® certified product (for 3000K and 4000K only) and Title 24 qualified. Dedicated 120V Models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications. California Title 24 Compliant, JA8 compliant, CEC Listed.

Warranty

3-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

Electrical

Equipped standard with 120V fixed output driver operating at 60 Hz.

Installation

Designed for wall mounting on 4" electrical J-Box.

Ordering Information

Example: WSS-14-13-120-930-NS

WSS	14	13	120	9	30	NS
Series	Form Factor	Rated Wattage	Driver Type	CRI	Color Temp	Finish
WSS Wall Sconce Square	14- 14" Length	14" Housing 13- 13W, (910 Lumens)	120- 120V ¹	9- 90+ CRI	30- 3000K ₃	BN- Brushed Nickel

Specifications and Dimensions subject to change without notice

Performance Summary

Input Voltage	120V
Input Frequency	50/60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table
Efficacy	70 LPW
CRI	90+, R9 > 0
Available CCT ¹	3000K
Color Consistency ²	5-step MacAdam Ellipse
Rated Life	50,000
L70 ³	> 72,000 hours or > 45,000 >
Power Factor	0.9
THD	< 20%
Dimming	N/A
Operating Temp.	-18°C to 40°C

Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)	Delivered Lumens	Efficacy (lm/W)
Frosted Acrylic	14"	WSS-14-13-120-MCT-BN	13W	910	70

NOTES:

- ¹ Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- ² Energy star listed
- ³ Quick ship: 3000K. Other CCTs may require a lead time or be special order
- ⁴ Typical color consistency. May vary or be changed.
- ⁵ L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information



Specifications and Dimensions subject to change without notice

WSS-14

