



Project	
Notes	
Type	Date
Cat. No.	

DOW™ Series Decorative Outdoor Pocket Lantern

DESCRIPTION
 The DOW LED wall light combines high-performance LEDs, a weather resistant aluminum housing along with a frosted glass diffuser for uniform illumination. Ideal use for security and general lighting. Provides lighting in residential, commercial, and hospitality applications.



DOW Series
 12W, 880 Lumens

Specification Features



Construction
 Rugged die cast aluminum housing withstands outdoor environments. Outer surface treated with durable power coating to provide resistance to corrosion, rust, weathering, and or degradation. Performance engineered internal heat dissipation fins provide superior thermal management for LED life and reliability.

Qualifications
 All luminaires are built to UL 1598 and 2108 standards, and bear appropriate ETL labels. Wet location labeling is standard. Emergency equipped fixtures labeled UL924. Adheres to LM70, LM80, and TM21 industry standards. ENERGY STAR® certified product (for 3000K and 4000K only). Dedicated 120V Models are FCC Title 47 CFR, Part 15, Class B for residential and commercial applications.

Electrical
 120V Driver operates at 60Hz.

Installation
 Designed for mounting on 4" electrical J-Box.

Warranty
 3-year limited warranty. See complete warranty for terms and exclusions. (Labor not included).

Rated Life 60,000 hours
 Limited Warranty 3 years
 Efficacy Up to 100 LPW

Quick Ship
 Made to Order

Ordering Information

Example: DOW-12-120-MCT-BL

DOW	11	120	MCT	BL	P
Series	Rated Wattage	Driver Type	Color Temperature	Driver Finish	Options
DOW Decorative Outdoor Pocket Lantern	12 - 12W, 880 Lumens	120 - 120V ¹	MCT - 3000K, 3500K, 4000K CCT Selectable, 80+ CRI	BL - Black ¹	P - Photocell ¹

Specifications and Dimensions subject to change without notice.

Performance Summary

Input Voltage	120V
Input Frequency	50/60 Hz
Rated Wattage	See Performance Table
Delivered Lumens	See Performance Table
Efficacy	> 100 LPW (typ.)
CRI	80+, R9 > 0
Available CCT ¹	3000K, 4000K, 5000K
Color Consistency ²	5-step MacAdam Ellipse
Rated Life	60,000 hours
L70 ³	> 72,000 hours or > 45,000
Power Factor	>0.99
THD	< 20%
Dimming	N/A
Operating Temp.	-18°C to 40°C

Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)	Delivered Lumens	Efficacy (lm/W)
Acrylic		DOW-12-120-880	12	880	88.8
		DOW-11-120-840	11W	1,100	100

NOTES:


- ¹ Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- ² Energy star listed
- ³ Quick ship: 3000K,5000K. Other CCTs may require a lead time or be special order
- ⁴ Typical color consistency. May vary or be changed.
- ⁵ L70 hours calculated based on LED package manufacturer LM80 report and ISTMT report of LED in luminaire. Stated values are for select catalog numbers. Contact manufacturer for detailed information
- ⁶ Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.

Specifications and Dimensions subject to change without notice.



Product Dimensions

DOP



GlobaLux
LIGHTING

© 2019 GlobaLux Lighting, LLC. All rights reserved. For informational purposes only. Reproduction in whole or part is prohibited without prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequences of its use. GlobaLux Lighting reserves the rights make changes in specification at any time without notice.

GlobaLux Lighting LLC
www.globaluxlighting.com
2037 S. Vineyard Ave
Ontario, CA 91761
Ph: 909-591-7506