



Project	
Notes	
Type	Date
Cat. No.	

LCXS™ Series

Bi-Color LED Combo Exit/Emergency Sign



#### APPLICATIONS

The LCXS is a newly designed Emergency/ Exit Light combining LED exit illumination with reliable LED Lamp heads. This attractive low-profile design offers maintenance-free, long life dependable application. LCXS/LED Combo unit is ideal for applications requiring both exit and emergency lighting. It's streamlined height makes the combo unit a great fit for above-the-door and other tight-fit applications.

#### Specification Features



##### Construction

Injection molded, engineering grade 5VA flame retardant, high impact resistant thermoplastic in white or black finish. Aesthetically pleasing, curved faced rounded corner design. EZ snap-out Chevron directional indicators.

##### Qualifications

Meets UL924, NFPA 11 life safety Code, NEC, OSHA Local and State Codes. UL listed for damp locations ( 0° C - 50° C ).

##### Warranty

5-year Limited Warranty on all electronics and housing.  
Battery pro rated for 5 years.

##### Electrical

Dual 120/277 voltage. Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing. 3.6 long-life, maintenance - free, rechargeable NiCad battery. Internal solid-state transfer switch automatically connects the internal battery to the LED lamp head for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharging a discharged battery in 24 hours.

##### Installation

Universal knockout pattern on back plate for wall mount. EZ-snap thermoplastic mounting canopy included provides top or end mount.

#### LCXS Series

LCXS-2-W-GR  
LCXS-2-B-GR

Limited Warranty 5-years

Quick Ship

LCXS-2-W-GR

#### Ordering Information

Example: LCXS-2-W-GR

LCXS	2	W	R		
<b>Series</b> <b>LCXS</b> LED Combo Exit/Emergency Sign	<b>Faces</b>  2	<b>Housing</b>  W- White B- Black	<b>Lettering</b>  GR- Green/Red	<b>Options</b>  Blank- 90 minute Battery AC- AC only	

Specifications and Dimensions subject to change without notice.

## Performance Summary

Input Voltage	120V/277V
Input Frequency	50/60 Hz
Rated Wattage	4W
Rated Life	60,000 hours
L70	> 72,000 hours or > 45,000
Power Factor	> 0.9
Operating Temp.	0°C to 40°C

## Performance Data

Lens Type	Form Factor	Catalog No.	Rated Wattage (W)
None		LCXS-2-W-GR	4
		LCXS-2-B-GR	4

### NOTES:

- <sup>1</sup> Made to order items. Minimum 90 day lead time. Minimum 500 order quantity.
- <sup>2</sup> Typical color consistency. May vary or be changed.
- <sup>3</sup> Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.
- <sup>4</sup> LCXS also has the option of Self Diagnostic and remote capable.



Specifications and Dimensions subject to change without notice.

## Product Dimensions

## LCXS

