

LOC-D Series

Installation Instructions

SAFETY INSTRUCTIONS

- 1. Read all safety precautions and installation instructions carefully before installing or servicing this fixture. Failure to comply with these instructions could result in potentially fatal electric shock and/or property damage.
- 2. It is recommended that all wiring be performed by a qualified electrician. This fixture must be wired in accordance with all national and local electrical codes.
- 3. Do not handle any turned on fixture with wet hands or while standing on a wet or damp surface.
- 4. Make sure that the power source conforms to the requirements of the fixture (see labels on fixture housing).
- 5. To reduce the risk of electrical shock, and to assure proper operation, this fixture must be properly grounded. To accomplish proper grounding, there must be a separate ground wire
- 6. This fixture is intended to be used for general outdoor lighting in damp or wet locations.

NEEDED TOOLS

- Safety Glasses
- Ruler/Tape Measure
- Flat Blade Screwdriver
- Phillips Screwdriver
- · Adjustable Wrench
- Drill
- 3/16" Drill Bit
- 3/32" Drill Bit
- Pliers

INSTRUCTIONS

Note: Please cut off the power before installation.

- 1. Fix the mounting bracket (1) to J-box.
- 2. Connect the wires, black/hot, white to Neutral wire, bare copper to Ground wire.
- 3. Use screws(2) to fix LED fixture (3) on the install bracket (1).

